



Optimizing Resource Allocation in 60 GHz Wireless Access Networks

George Athanasiou, Pradeep Chathuranga Weeraddana,
Carlo Fischione

Electrical Engineering School and Access Linnaeus Center,
KTH Royal Institute of Technology, Stockholm, Sweden
{georgioa, chatw, carlofi}@kth.se

Ericsson Research 06.03.13

Group



Carlo Fischione
Associate Professor



Pradeep Chathuranga
Weeraddana
Research Associate



George Athanasiou
Research Associate



Marco Levorato
Research Associate



Piergiuseppe Di Marco
Research Associate



Martin Jakobsson
PhD Student



Yuzhe Xu
PhD Student

Group Activities

- Research interests

- Wireless networking analysis and optimization with applications to 3/4/5G
- Wireless sensor networks
- Smart grids
- Wireless industrial control

- Research projects

- European Institute of Technology, Car2X Communications, 2013
- European Institute of Technology, LTE in Smart Grids, 2013
- Hycon2 EU project, Highly-complex and networked control systems, 2010-2014
- Hydrobionets EU project, Autonomous control of large-scale water treatment plants based on self-organized wireless BIOMEM sensor and actuator networks, 2011-2014
- Swedish Research Council, In-Network Optimization, 2012-2014

- Educational activities

- Teaching at PhD, Master and Bachelor level

Outline

- Past, Present and Future in wireless communications
- 60 GHz millimeterWave wireless technology
- Optimizing resource allocation
- Distributed client association (DAA)
- Numerical analysis of DAA
- Conclusions and open research topics

Outline

- Past, Present and Future in wireless communications
- 60 GHz millimeterWave wireless technology
- Optimizing resource allocation
- Distributed client association (DAA)
- Numerical analysis of DAA
- Conclusions and open research topics

Growth of Mobile Traffic




Source: Cisco VNI Mobile Forecast, 2013

Growth of Mobile Traffic



2012: 70% mobile traffic growth compared to 2011

Growth of Mobile Traffic



2012: 51% of the mobile traffic was video

Growth of Mobile Traffic




2012: 12 times the entire global internet traffic in 2000

Growth of Mobile Traffic




2017: 13 times higher compared to 2012

LTE Deployment




LTE Deployment




2012: 0.9% of mobile connections

LTE Deployment




End of 2013: # of mobile connected devices > earth population

LTE Deployment




2017: 4G will represent 10% of connections and 45% of mobile traffic

LTE Deployment



2017: 2/3 will be video

LTE Deployment



2017: 2.7 GB mobile traffic per smartphone per month

Mobile Traffic Offloading



The amount of traffic offloaded from smartphones will be 46%, and the amount of traffic offloaded from tablets will be 71% in 2017 (Cisco, 2013)

90% of all cellular base stations will be small cells by 2016 (IEEE Spectrum Magazine, Informa Telecoms & Media, 2013)

Priorities

- High bandwidth

- High coverage



- Green

- Cheap



Evolution or Revolution?

- Infrastructure moves closer to the users
- Devices communicate directly (D2D)
- Base station is “dying”
- Heterogeneous networks converge

Mobile Data Offloading



Mobile Data Offloading





Are there better solutions for mobile data offloading?

Outline

- Past, Present and Future in wireless communications
- **60 GHz millimeterWave wireless technology**
- Optimizing resource allocation
- Distributed client association (DAA)
- Numerical analysis of DAA
- Conclusions and open research topics



60 GHz Wireless Access Networks

- Unlicensed short range transmissions in the 60 GHz millimeter wave (mmW) band
- Achieve Gbps communication
- Reduced interference
- Low-cost mmW transceivers




MillimeterWave Band

- History (J.C. Bose, 1897)
- High path loss
- High oxygen absorption




60 GHz Wireless Standards


- IEEE 802.11ad
- WiGig
- IEEE 802.15.3c
- WirelessHD
- ECMA-387



Applications



60 GHz to the Mobile




- 60 GHz small base stations (eg. on lamp posts)
- Downlink offload traffic in 60 GHz band with uplink LTE feedback
- 60 GHz radio on mobile device in receive-only mode


Outline

- Past, Present and Future in wireless communications
- 60 GHz millimeterWave wireless technology
- **Optimizing resource allocation**
- Distributed client association (DAA)
- Numerical analysis of DAA
- Conclusions open research topics

Optimizing Client Association in 60 GHz Wireless Access Networks



Optimizing Client Association in 60 GHz Wireless Access Networks




Optimizing Client Association in 60 GHz Wireless Access Networks

- **Goal:** Minimize the maximum access point (AP) utilization in the network and ensure fair load distribution
- **Solution:** Distributed algorithm for client association based on Lagrangian duality theory and subgradient methods
- **Results:** Theoretical and numerical analysis

G. Athanasiou, P. C. Weeraddana, C. Fischione and L. Tassiulas, "Optimizing Client Association in 60 GHz Wireless Access Networks", *arXiv:1301.2723, Cornell University Library*, 2013 [Online]. Available: <http://arxiv.org/abs/1301.2723>

System Model



| | |
|-----------------|---|
| W | System bandwidth |
| P_{ij} | Transmission power of AP i to client j |
| G_{ij} | Power gain from AP i to client j |
| N_0 | Power spectral density of the noise |
| I_j | Interference spectral density at client j |
| \mathcal{M}_i | Set of clients that can be associated to AP i |
| \mathcal{N}_j | Set of APs that client j could be associated with |

- $\mathcal{N} = \{1, \dots, N\}$ APs and $\mathcal{M} = \{1, \dots, M\}$ clients
- Achievable rate from AP i to client $j \in \mathcal{M}_i$ is

$$R_{ij} = W \log_2 \left(1 + \frac{P_{ij} G_{ij}}{(N_0 + I_j) W} \right)$$

- Q_j is the demanded data rate of client j

System Model

- Channel utilization between AP i and client j is

$$\beta_{ij} = \frac{Q_j}{R_{ij}}$$

- Utilization of AP i is


$$\sum_{j \in \mathcal{M}_i} \beta_{ij} x_{ij}$$

- $(x_{ij})_{j \in \mathcal{M}_i}$ are binary decision variables, which indicate the client association

$$x_{ij} = \begin{cases} 1 & \text{if client } j \text{ is associated to AP } i \\ 0 & \text{otherwise} \end{cases}$$

Client Association Problem Formulation

$$\begin{aligned} & \text{minimize} && \max_{i \in \mathcal{N}} \sum_{j \in \mathcal{M}_i} \beta_{ij} x_{ij} \\ & \text{subject to} && Q_j x_{ij} \leq R_{ij}, \quad i \in \mathcal{N}, j \in \mathcal{M}_i \\ & && \sum_{i \in \mathcal{N}_j} x_{ij} = 1, \quad j \in \mathcal{M} \\ & && x_{ij} \in \{0, 1\}, \quad j \in \mathcal{M}, i \in \mathcal{N}_j \end{aligned}$$



- Variable: $(x_{ij})_{i \in \mathcal{N}, j \in \mathcal{M}_i}$
- Main problem parameters: $(\beta_{ij})_{i \in \mathcal{N}, j \in \mathcal{M}_i}$, $(Q_j)_{j \in \mathcal{M}}$, $(R_{ij})_{i \in \mathcal{N}, j \in \mathcal{M}_i}$
- Constraints: a) The demand of client j is less or equal to the achievable rate from AP i to client j , b) Client j can only be assigned to one AP, c) The decision variables are binary


Equivalent Epigraph Form

minimize t

subject to $\sum_{j \in \mathcal{M}_i} \beta_{ij} x_{ij} \leq t, i \in \mathcal{N}$

$\sum_{i \in \mathcal{N}_j} x_{ij} = 1, j \in \mathcal{M}$


$x_{ij} \in \{0, 1\}, j \in \mathcal{M}, i \in \mathcal{N}_j$



- Variable: $(x_{ij})_{i \in \mathcal{N}, j \in \mathcal{M}_i}$ and t
- Main problem parameters: $(\beta_{ij})_{i \in \mathcal{N}, j \in \mathcal{M}_i}$
- Mixed integer linear program (MILP)


Solution Method Challenges

- Existing **MILP** solvers are **centralized**
- Typically based on global branch and bound algorithms \Rightarrow the **worst-case complexity grows exponentially** with the problem size
- **Even small** problems, with a few tens of variables, can take a **very long time**



Solution Method Challenges

- Existing **MILP** solvers are **centralized**
- Typically based on global branch and bound algorithms \Rightarrow the **worst-case complexity grows exponentially** with the problem size
- **Even small** problems, with a few tens of variables, can take a **very long time**
- Our approach: **Lagrangian duality + Subgradient methods** \Rightarrow **decentralized**




Lagrangian Duality

Partial Lagrangian

$$\begin{aligned}
 L(t, \mathbf{x}, \boldsymbol{\lambda}) &= t + \sum_{i \in \mathcal{N}} \lambda_i \left(\sum_{j \in \mathcal{M}_i} \beta_{ij} x_{ij} - t \right) \\
 &= t \left(1 - \sum_{i \in \mathcal{N}} \lambda_i \right) + \sum_{j \in \mathcal{M}} \sum_{i \in \mathcal{N}_j} \beta_{ij} \lambda_i x_{ij}
 \end{aligned}$$

$\boldsymbol{\lambda} = (\lambda_i)_{i \in \mathcal{N}}$: multipliers for the first set of inequality constraints



Lagrangian Duality

Partial Lagrangian


$$\begin{aligned}
 L(t, \mathbf{x}, \boldsymbol{\lambda}) &= t + \sum_{i \in \mathcal{N}} \lambda_i \left(\sum_{j \in \mathcal{M}_i} \beta_{ij} x_{ij} - t \right) \\
 &= t \left(1 - \sum_{i \in \mathcal{N}} \lambda_i \right) + \sum_{j \in \mathcal{M}} \sum_{i \in \mathcal{N}_j} \beta_{ij} \lambda_i x_{ij}
 \end{aligned}$$

$\boldsymbol{\lambda} = (\lambda_i)_{i \in \mathcal{N}}$: multipliers for the first set of inequality constraints

Dual function

$$g(\boldsymbol{\lambda}) = \inf_{\substack{t \in \mathbb{R} \\ \mathbf{x} \in \mathcal{X}}} L(t, \mathbf{x}, \boldsymbol{\lambda})$$


$$\mathcal{X} = \left\{ \mathbf{x} = (x_{ij})_{j \in \mathcal{M}, i \in \mathcal{N}_j} \mid \sum_{i \in \mathcal{N}_j} x_{ij} = 1, \quad x_{ij} \in \{0, 1\}, \quad j \in \mathcal{M}, i \in \mathcal{N}_j \right\}.$$



Lagrangian Duality

Dual problem

$$\begin{aligned} & \text{maximize} \quad g(\boldsymbol{\lambda}) = \sum_{j \in \mathcal{M}} g_j(\boldsymbol{\lambda}) \\ & \text{subject to} \quad \sum_{i \in \mathcal{N}} \lambda_i = 1 \\ & \quad \lambda_i \geq 0, \quad i \in \mathcal{N} \end{aligned}$$



- Variables: $\boldsymbol{\lambda} = (\lambda_i)_{i \in \mathcal{N}}$
- $g_j(\boldsymbol{\lambda})$ is the optimal value of the **subproblem**


$$\begin{aligned} & \text{minimize} \quad \sum_{i \in \mathcal{N}_j} \beta_{ij} \lambda_i x_{ij} \\ & \text{subject to} \quad \mathbf{x}_j \in \mathcal{X}_j , \end{aligned}$$

with the variable \mathbf{x}_j .

Lagrangian Duality

Dual problem

$$\begin{aligned} & \text{maximize} \quad g(\boldsymbol{\lambda}) = \sum_{j \in \mathcal{M}} g_j(\boldsymbol{\lambda}) \\ & \text{subject to} \quad \sum_{i \in \mathcal{N}} \lambda_i = 1 \\ & \quad \lambda_i \geq 0, \quad i \in \mathcal{N} \end{aligned}$$



- Variables: $\boldsymbol{\lambda} = (\lambda_i)_{i \in \mathcal{N}}$
- $g_j(\boldsymbol{\lambda})$ is the optimal value of the **subproblem**

$$\begin{aligned} & \text{minimize} \quad \sum_{i \in \mathcal{N}_j} \beta_{ij} \lambda_i x_{ij} \\ & \text{subject to} \quad \mathbf{x}_j \in \mathcal{X}_j , \end{aligned}$$


→ solved @ client j

with the variable \mathbf{x}_j .

Subgradient Method

Subgradient method to solve dual problem

$$\boldsymbol{\lambda}^{(k+1)} = P(\boldsymbol{\lambda}^{(k)} - \alpha_k \mathbf{u}^{(k)})$$



- P : Euclidean projection onto the unit simplex $\Pi = \{\boldsymbol{\lambda} \mid \sum_{i \in \mathcal{N}} \lambda_i = 1, \lambda_i \geq 0\}$
- $\alpha_k > 0$ is the k th step size
- $\mathbf{u}^{(k)} = \left(u_i^{(k)}\right)_{i \in \mathcal{N}}$: a subgradient of $-g$ at $\boldsymbol{\lambda}^{(k)}$, where

$$u_i^{(k)} = - \sum_{j \in \mathcal{M}_i} \beta_{ij} x_{ij}^*,$$

and $(x_{ij}^*)_{j \in \mathcal{M}_i}$ is the solution of the i th subproblems with $\boldsymbol{\lambda} = \boldsymbol{\lambda}^{(k)}$

Subgradient Method

Subgradient method to solve dual problem


$$\boldsymbol{\lambda}^{(k+1)} = P(\boldsymbol{\lambda}^{(k)} - \alpha_k \mathbf{u}^{(k)})$$

- P : Euclidean projection onto the unit simplex $\Pi = \{\boldsymbol{\lambda} \mid \sum_{i \in \mathcal{N}} \lambda_i = 1, \lambda_i \geq 0\}$
- $\alpha_k > 0$ is the k th step size
- $\mathbf{u}^{(k)} = \left(u_i^{(k)}\right)_{i \in \mathcal{N}}$: a subgradient of $-g$ at $\boldsymbol{\lambda}^{(k)}$, where

price update

$$u_i^{(k)} = - \sum_{j \in \mathcal{M}_i} \beta_{ij} x_{ij}^*,$$



and $(x_{ij}^*)_{j \in \mathcal{M}_i}$ is the solution of the i th subproblems with $\boldsymbol{\lambda} = \boldsymbol{\lambda}^{(k)}$





Outline

- Past, Present and Future in wireless communications
- 60 GHz millimeterWave wireless technology
- Optimizing resource allocation
- **Distributed client association (DAA)**
- Numerical analysis of DAA
- Conclusions and open research topics



DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration





DAA Illustration



DAA Illustration



DAA Illustration



DAA Properties

Proposition

Let $g_{\text{best}}^{(k)}$ denote the best dual objective value found after k subgradient iterations, i.e., $g_{\text{best}}^{(k)} = \max\{g(\boldsymbol{\lambda}^{(1)}), \dots, g(\boldsymbol{\lambda}^{(k)})\}$. Then, $\forall \epsilon > 0$
 $\exists n \geq 1$ such that $\forall k \ k \geq n \Rightarrow (d^* - g_{\text{best}}^{(k)}) < \epsilon$.


Theorem

The optimal duality gap of the mixed integer linear program is bounded as follows:

$$p^* - d^* \leq (N + 1)(\varrho + \max_{j \in \mathcal{M}} \varrho_j) ,$$


where $\varrho = \max_{i \in \mathcal{N}, j \in \mathcal{M}_i} \beta_{ij}$ and $\varrho_j = \min_{i \in \mathcal{N}_j} \beta_{ij}$. Moreover, the relative duality gap $(p^* - d^*)/p^*$ diminishes to 0 as $M \rightarrow \infty$.

Implementation Over Existing Standards



- Initially the clients follow the RSSI-based association policy that IEEE 802.11ad and IEEE 802.15.3c define
- DAA** is periodically executed to correct possible suboptimal client associations by reallocating the available resources

Implementation Over Existing Standards



- APs trigger the initialization of **DAA** by setting a special bit into the beacon frame
- Information exchange is performed through the control frames or piggy-backing the data frames



Outline

- Past, Present and Future in wireless communications
- 60 GHz millimeterWave wireless technology
- Optimizing resource allocation
- Distributed client association (DAA)
- **Numerical analysis of DAA**
- Conclusions and open research topics

Numerical Analysis

- Consider a multi-user multi-cell environment
- Compare DAA to
 - Random association
 - RSSI-based association (IEEE 802.11)
 - Optimal association (IBM CPLEX)
- Measure
 - Convergence
 - Scalability
 - Time efficiency
 - Fairness

Topologies




| λ | Wavelength |
|-----------|------------------------------|
| d_0 | Far field reference distance |
| η | Path loss exponent |

- SNR operating point at a distance d from any AP

$$\text{SNR}(d) = \begin{cases} P_0 \lambda^2 / (16\pi^2 N_0 W) & d \leq d_0 \\ P_0 \lambda^2 / (16\pi^2 N_0 W) \cdot (d/d_0)^{-\eta} & \text{otherwise} \end{cases}$$

- Radius of each cell r is chosen such that $\text{SNR}(r) = 10 \text{ dB}$
- Clients are uniformly distributed at random, among the circular cells


Convergence of DAA




- Average primal objective value from **DAA** after k subgradient iterations: $P^{(k)} = (1/\bar{T}) \sum_{T=1}^{\bar{T}} p_{\text{best}}^{(k)}(T)$
- Average dual optimal value by **DAA**: $D^* = (1/\bar{T}) \sum_{T=1}^{\bar{T}} d^*(T)$

Convergence of DAA

3 APs, 30 clients




10 APs, 100 clients




- Convergence time is affected by the number of APs and clients: The smaller the network, the faster **DAA** converges

Scalability of DAA





- Performance improvement increases while the network becomes bigger and more loaded
- **DAA** performs close to optimal

Scalability of DAA



- Considering constant load, the average objective value decreases while the number of APs increases
- **DAA** performs close to optimal

Optimality of DAA




- Average relative duality gap:

$$\text{Ave-RDG} = (1/\bar{T}) \sum_{T=1}^{\bar{T}} (p^*(T) - d^*(T)) / p^*(T)$$

- Average relative duality gap taking into account the best primal feasible objective value from **DAA** after K iterations at time slot T :
- $$\text{Ave-RDG-best-achieved} = (1/\bar{T}) \sum_{T=1}^{\bar{T}} (p_{\text{best}}^{(K)}(T) - d^*(T)) / p_{\text{best}}^{(K)}(T)$$

Fairness Achieved by DAA





- Jain's fairness index:

$$J^{(k)}(T) = \left(\sum_{i \in \mathcal{N}} Y_i^{(k)}(T) \right)^2 / \left(N \sum_{i \in \mathcal{N}} Y_i^{(k)}(T)^2 \right),$$

$Y_i^{(k)}(T) = \sum_{j \in \mathcal{M}_i} \beta_{ij} x_{ij}^{(k)}(T)$ and $x_{ij}^{(k)}(T)$ is the solution (best feasible) resulted from **DAA** at time slot T after k iterations

Speed and Resources Used by DAA



- Empirical CDF plots of the number of iterations for $M = 100, 200, 300$ clients, with $N = 10$ APs
- Trade-off between optimality and complexity

Outline

- Past, Present and Future in wireless communications
- 60 GHz millimeterWave wireless technology
- Optimizing resource allocation
- Distributed client association (DAA)
- Numerical analysis of DAA
- **Conclusions and open research topics**

Conclusions

- 60 GHz wireless technology: characteristics, benefits, challenges, applications
- Distributed association algorithm (DAA) for optimizing resource allocation in 60 GHz wireless access networks
- Performance evaluation of **DAA**: Asymptotically optimal, convergence, time efficiency and fairness
- Integration of **DAA** into current standards

Open Research Topics

- 60 GHz channel modeling
- Medium Access Control (MAC)
- Connectivity maintenance, blockage and directivity
- Coexistence and cooperation with existing wireless technologies
- Multi-hop communications
- ...

Thank you



Optimizing Resource Allocation in 60 GHz Wireless Access Networks

George Athanasiou, Pradeep Chathuranga Weeraddana,
Carlo Fischione

Electrical Engineering School and Access Linnaeus Center,
KTH Royal Institute of Technology, Stockholm, Sweden
{georgia, chatw, carlofi}@kth.se

Ericsson Research 06.03.13